



Beamless Low Profile Lift

Industrial Duty Integrated with a New Ultra Modern Appeal

- All Aluminum and Stainless Steel Construction
- Solid Billet Aluminum Grooved Winders with Exclusive SeArmor Corrosion Resistant Coating
- Ultra High Speed (H2)
- Extended Lift Travel
- Stainless Steel Motors
- Long-Life Bearings
- Aluminum Bunks
- Low-Profile Beamless Design
- 10 Year Limited Warranty

Options:

- Wireless Remote Control
- Limit Switch with Auto Stop

*** See our "Complete List of Other Accessories"



Specifications

Size	Horse Power	Volt and Amperage	Cable Size	Winding Area	Vertical Travel	Speed	Max. Beam	Lifter Dimensions	Bunks	Pile Size
12,000 lb.	(2) 1 HP	240V/20A	5/16" Stainless Steel	SeArmor Grooved Winders	12'	20"	10' 0"	8" I-Beam	12'0" Aluminum Bunks	(4) 10"
12,000 lb. H2 High Speed	(2) 1.5 HP	240V/25A	5/16" Stainless Steel	Solid SeArmor Grooved Winders	12'	41"	10' 0"	8" I-Beam	12'0" Aluminum Bunks	(4) 10"
16,000 lb.	(2) 1.5 HP	240V/25A	5/16" Stainless Steel	SeArmor Grooved Winders	12'	20"	12' 0"	10" I-Beam	12'0" Aluminum Bunks	(4) 10"
16,000 lb. H2 High Speed	(2) 2 HP	240V/30A	5/16" Stainless Steel	Solid SeArmor Grooved Winders	12'	41"	12' 0"	10" I-Beam	12'0" Aluminum Bunks	(4) 10"
24,000 lb.	(4) 3/4 HP	240V/25A	5/16" Stainless Steel	SeArmor Grooved Winders	12'	17"	12' 6"	12" I-Beam	3" x 12" x 18' Carpeted Wood Bunks	(4) 10" Driven
24,000 lb. H2 High Speed	(4) 1.5 HP	240V/50A	5/16" Stainless Steel	SeArmor Grooved Winders	12'	43"	12' 6"	12" I-Beam	3" x 12" x 18' Carpeted Wood Bunks	(4) 10" Driven
30,000 lb.	(4) 1 HP	240V/30A	3/8" Stainless Steel	SeArmor Grooved Winders	12'	17"	12' 6"	12" I-Beam	3" x 12" x 18' Carpeted Wood Bunks	(4) 12" Driven
30,000 lb. H2 High Speed	(4) 2 HP	240V/50A	3/8" Stainless Steel	SeArmor Grooved Winders	12'	43"	12' 6"	12" I-Beam	3" x 12" x 18' Carpeted Wood Bunks	(4) 12" Driven

* Specifications are subject to change without notice *