



G6 SuperFast Direct Drive Aluminum Elevator Lifts

Industrial Duty Integrated with a New Ultra Modern Appeal

- All Aluminum and Stainless Steel Construction
- Low Draft Design
- Very Modern Compact Drive Units
- Aluminum Bunks (Standard up to 20,000 lbs. if applicable)
- Stainless Steel Cables
- Adjustable Heavy Duty Guide Poles
- Piling or Seawall Mount
- Standard Angle is 25° (Available in Various Angles including Vertical)
- 12 Year Limited Warranty

Options:

- SEArmor Corrosion Resistant Winders for Long Lasting Durability
- Wireless Remote Control
- Auto Stop & Limit Switch
- Complete Disconnect Switch
- Stainless Steel Wash Down Motors
- Underwater Bracing (for Deepwater Applications)
- Cable Retention System



Specifications

***See our "Complete list of Other Accessories"

| Size | Horse Power | Volt and Amperage | Cable Size and Length | Vertical Travel | Track Size | Max. Beam | Cradle Dimensions | Bunks | Pile Size |
|------------|----------------------------------|-------------------|--------------------------------|-----------------|--------------------------|-----------|-------------------|----------------------------------|-----------------------|
| 5,000 lb. | (2) 1 HP Stainless Steel* | 240V/20A | 5/16" x 30' Stainless Steel | 12' | 6" x 4" x 25' I-Beam | 8' 0" | 7' Dual Forks | 3" x 8" x 12' Aluminum Bunks | 8" Min. Tied Back |
| 7,000 lb. | (2) 1 1/2 HP Stainless Steel* | 240V/30A | 5/16" x 30' Stainless Steel | 12' | 8" x 5" x 25' I-Beam | 8' 0" | 7' Dual Forks | 3" x 8" x 12' Aluminum Bunks | 8" Min. Tied Back |
| 10,000 lb. | (2) 2 HP Stainless Steel* | 240V/30A | 5/16" x 30' Stainless Steel | 12' | 8" x 5" x 25' I-Beam | 9' 0" | 8' Dual Forks | 3" x 8" x 12' Aluminum Bunks | 10" Min. Tied Back |
| 12,000 lb. | (2) 2 HP Stainless Steel* | 240V/30A | 5/16" x 42' Stainless Steel | 11' | 10" x 6" x 25' I-Beam | 10' 0" | 8' Dual Forks | 3" x 10" x 14' Aluminum Bunks | 10" Min. Tied Back |
| 14,000 lb. | (2) 2 HP Stainless Steel* | 240V/30A | 5/16" x 42' Stainless Steel | 11' | 10" x 6" x 25' I-Beam | 10' 0" | 8' Dual Forks | 3" x 10" x 14' Aluminum Bunks | 10" Min. Tied Back |
| 15,000 lb. | (2) 2 HP Stainless Steel* | 240V/30A | 5/16" x 42' Stainless Steel | 11' | 10" x 6" x 25' I-Beam | 10' 0" | 8' Dual Forks | 3" x 10" x 14' Aluminum Bunks | 10" Min. Tied Back |
| 17,000 lb. | (2) 2 HP Stainless Steel* | 240V/30A | 5/16" x 56' Stainless Steel | 11' | 12" x 7" x 25' I-Beam | 11' 0" | 10' Dual Forks | 3" x 10" x 14' Aluminum Bunks | 12" Min. Tied Back |
| 20,000 lb. | (2) 2 HP Stainless Steel* | 240V/30A | 5/16" x 56' Stainless Steel | 11' | 12" x 7" x 25' I-Beam | 12' 0" | 10' Dual Forks | 3" x 10" x 14' Aluminum Bunks | 12" Min. Tied Back |

*Stainless Steel Motors are Standard on all Direct Drive and H2 High Speed Direct Drive Lifts Only *240V Incoming Power is Recommended.